

## *Building Panel Presentation*

### I. GLAZING AND IN-FILL PANELS

- A. **Omega-Ply:** Wood Core, Aluminum Faced Panel
  - 1. Description
  - 2. History
  - 3. Typical Uses
- B. **Omega-Lite:** Better performing panel – impervious to water Damage
- C. **ThermoLite and Omega Foam-Ply:** Insulated infill and glazing panels

### II. PANELS FOR SPANDREL APPLICATIONS:

- A. **System I – (Extrusions) (\$\$)**
  - 1. Applications
  - 2. Installation Overview
  - 3. Colors
- B. **System IV – (Rout & Return) (\$\$\$)**
  - 1. Applications
  - 2. Installation Overview
  - 3. Colors
- C. **System VI - (Clip and Caulk) (\$)**
  - 1. Applications
  - 2. Installation Overview
  - 3. Colors

### III. SUMMARY:

- A. **Color Selections:**
  - 1. **Economy (\$)** -
    - .013” Stucco only - Currently 10 colors available
    - 10 Year Colorfast – NQ20 Paint System
  - 2. **Standard (\$\$)**
    - .024” Painted Aluminum Skins (Smooth or Stucco) - 6 Colors
    - 10 Year Colorfast – NQ20 Paint System
  - 3. **Premium (\$\$\$)**
    - .032” Painted Aluminum (Smooth or Stucco) – 27 Colors
    - 20-Year Colorfast – Kynar 500 Paint System
  - 4. **Anodized (\$\$\$\$)**
    - Limited Warranty Available
    - Dark Bronze and Clear Satin
  - 5. **Custom Colors (\$\$\$\$\$)**
    - Paint color matched to your samples
    - Minimum Order: 800 sq.ft.
- B. **Certified Installers:**
- C. **Questions & Follow-up**